

SC-95TN

EN 54-24



The SC-95TN is a high performance 24W coaxial ceiling loudspeaker. Its broad frequency range, low distortion, and high sound pressure level ensures the delivery of intelligible voice and excellent sound. The stylish low profile and white color design allows it to blend easily with most applications, such as hotels, shopping malls, conference rooms and exhibition halls.

This coaxial ceiling loudspeaker is EN54-24 certified, what ensures that, in the event of a fire, damage to the loudspeaker does not result in failure of the loudspeaker circuit which is connected.

Features of the SC-95TN :

- It is EN54-24 certified
- Intelligible voice and excellent sound reproduction
- Easy blending with any decorations
- Robust metal case with fireproof dome
- Simple power setting and wiring

Technical Specifications:

Model	LDASC95TNS01
Max power	36 W
Rated power	24 W
Power taps @ 100V	24 W / 12 W / 6 W / 3 W / 4Ω
SPL at 24W/1W(100 Hz-10 kHz,1m)	103dB / 91dB
SPL at 24W/1W(100 Hz-10 kHz,4m)	91dB / 79dB
Frequency response (- 10 dB)	120 Hz-20K Hz
Rated input voltage	100 V / 70 V
Rated impedance	0.42k Ω / 0.83kΩ / 1.67k Ω / 3.33k Ω/4Ω
Connection	Fire-resistant cable
Dimensions	Φ 226 mm × 129 mm
Hole cut-out size	Φ195mm
Weight	2.25 kg
Colour	White (RAL9003)/ Red (RAL3000)
Speaker size	6.5"
Operating temperature	-25°C to +55°C
Storage temperature	-40°C to +70°C
Relative humidity	up to 95%